Wheat and Rice Flour Moisture Tester PRv-930



Kett has been researching and providing moisture measurement technology and long selling Riceter series since 1961. This special experience has become the core of the technology of our grain moisture testers. Using accurate and reliable moisture testers will improve the quality of your grain and maximize your profits. The investment in Kett moisture testers will meet your expectations.

Features

- Easy operation & comfortable design with non-slip treads
- Large and highly visible backlit LCD
- Constant grinding pressure mechanism to keep accuracy for long time
- Comes with hard carrying case
- Durable even in tough field conditions
- Displays average moisture value instantly
- Equipped with auto power off function

Specification

Measurement method	Electrical resistance
Accuracy	Flour : 0.25% (SEC, full range) Grain : 0.5% (SEC, below 20%)
Operating temperature	0 to +40˚C
Display	Digital LCD with backlight illuminator Minimum display digit, 0.1%
Power source	1.5V batteries x 4
Dimensions and Weight	(Only main unit) 164(W)x94(D)x65(H)mm, approx. 0.44kg (Shipment gross) 310(W)x150(D) x120(H)mm, approx. 1.8kg
Accessories	Sample tray for grain (2), Sample tray for flour (2), Metal plate (3), Spoon with tweezers (1), Cleaning brush (2 types), AA size Battery (4), Carrying case (1), Operating manual (1), Inspection certificate (1)
Options	Checker for Riceter

Applications, Measuring range & Accuracy

No.	Applications	Abbreviation	Measurement range (%)	Accuracy (SEC)*1
1	Wheat flour	WFLO	11-18%	0.25%
2	Wheat	WHEA	9-30%	0.50%
3	Rice flour	RFLO	8-18%	0.25%
4	Long milled rice	LMR	10-20%	0.50%
5	Short milled rice	SMR	10-20%	
6	Long paddy	LPAD	10-35%	
7	Short paddy	SPAD	10-30%	

* Compared to reference drying oven method in the range less than 20%
* SEC : Standard Error of Calibration curve

Options



Checker for Riceter

KETT ELECTRIC LABORATORY Co. Ltd.
1-8-1 Minami-Magome, Ota-ku, Tokyo 143-8507, JAPAN
☎ +81-3-3776-1121
+81-3-3772-3001
https://www.kett.co.jp/english/contacts/

2403·SN·XX·0100·000